

Manometer-Druckknopfhahn button valve for pressure gauge

Type: 0805



Technische Daten:

BAUFORM:

Manuell betätigter Druckknopfhahn zur Druckmessung für GAS für Druckluft, Wasser und neutrale Flüssigkeiten

ANSCHLUSS:

Innengewinde gem. ISO 7/1

NENNDRUCK:

MOP 5 – GAS
16 bar - für Druckluft, Wasser und neutrale Flüssigkeiten

WERKSTOFFE:

Gehäuse: Messing CW617N - vernickelt
Druckknopf: Messing CW614N - vernickelt
O-Ring: NBR
Feder: AISI 302
Kappe: Messing CW614N - vernickelt

TEMPERATUR:

- 20°C/+60°C für GAS
- 20°C/+100°C für Druckluft, Wasser und neutrale Flüssigkeiten

ZULASSUNG:

• DVGW-G (Zertifikat Nr.: DG-4315CT0161)

Specification:

DESIGN:

manually operated button valve for pressure gauge for GAS for compressed air, water and liquids in general

CONNECTION:

Female thread acc. to ISO 7/1

PRESSURE RANGE:

MOP 5 – for GAS
16 bar - for compressed air, water and liquids in general

MATERIALS:



body: brass CW617N – nickel plated
button: brass CW614N – nickel plated
O-Ring: NBR
spring: AISI 302
cup: brass CW614N – nickel plated

TEMPERATURE:

- 20°C/+60°C for GAS
- 20°C/+100°C for compressed air, water and liquids in general

APPROVAL:

• DVGW-G (cert. No.: DG-4315CT0161)



Abmessungen / dimensions:

Größe/size	DN	MOP	A	B	C	D	E	F closed	F open	Sw
1/4"	8	5	25	25	50	23	18,5	30,5	22,5	22
3/8"	10	5	25	25	50	23	18,5	30,5	22,5	22
1/2"	15	5	34	34	68	27,5	31	50	36,5	27